

Tough Coat

Rust and Corrosion Prevent Coating

Available Colors : White, Red, Black, Blue

DESCRIPTION:

VOC compliant. High solids formula offers superior coverage. Helps prevent rust and corrosion on metal surfaces. Protects against gas, oil, grease and mild acids. Use both indoor and out door. Quick Drying, lead-free formula.

DIRECTIONS:

1. Surface must be clean, dry before painting. Protect surrounding areas from spray mist. For maximum protection, prime bare or rusted metal surfaces with primer. Match appropriate primer color with topcoat
2. For best results use when can is between 70°F and 90°F (21°C and 32°C)
3. Shake can at least one minute before and occasionally during use.
4. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Longer distances may cause low gloss, poor hide and poor adhesion. Several light coats will give a better finish than one heavy coat.
5. If clogging develops, turn spray head 1/4 turn or remove and clean button slot. Do not stick objects into can opening. With can and spray head pointed away from you, reinsert spray-head with a gentle twisting motion.
6. Recoat - For best results recoat within 1 hour or after 48 hours. This time varies with curing temperature, humidity, and film thickness. Test a small hidden area before recoating.
7. To clear spray head for future use, turn can right side up and spray for 3 seconds.
8. Discard empty can in trash pick up. Do not incinerate or compact.



HMIS	
Health	2
Flammability	4
Reactivity	3
Personal Protection (PPE)	X